


اطلاعات فنی | TECHNICAL DATA

PERFORMANCES		Model	663/F4**	693/F4**	783/F6	793/F6	863/F6	873/F8	883/F8	893/F10
NOMINAL COOLING CAPACITY (1)	ECO.M(3)	kW	247	-	434	478	522	606	652	757
TOTAL NOMINAL ABSORBED POWER (1)		kW	60,90	-	112,20	128,80	148,40	155,00	184,40	198,30
EER (1)		kW/kW	3,58	-	3,48	3,39	3,25	3,54	3,25	3,46
NOMINAL WATER FLOW		m3/h	42,53	-	74,57	82,29	89,80	104,24	112,15	130,15
EVAPORATOR PRESSURE DROP		kPa	22	-	71	60	70	64	71	64
NOMINAL COOLING CAPACITY (6)	NE.M(3)	kW	297	-	515	568	600	720	771	913
TOTAL NOMINAL ABSORBED POWER (6)		kW	61,0	-	113,0	133,0	145,0	157,0	182,0	202,0
EER (6)		kW/kW	4,29	-	4,11	3,91	3,82	4,15	3,89	4,1
NOMINAL WATER FLOW		m3/h	36,50	-	63,30	69,80	73,80	88,40	94,70	112,20
EVAPORATOR PRESSURE DROP		kPa	17	-	52	61	48	67	51	48
HYDRAULIC SECTION										
WATER FLOW RANGE		m3/h	30÷80	-	43÷86	144÷287	52÷103	72÷144	79÷158	82÷163
MAXIMUM PUMP ABSORBED POWER (OPTION WP OR DP)	P3 (2)	kW	8,3	-	10,2	10,2	16,2	16,2	16,2	16,2
MAXIMUM PUMP ABSORBED CURRENT (OPTION WP OR DP)		A	14,1	-	17,4	17,4	26,6	26,6	26,6	26,6
MAXIMUM PUMP ABSORBED POWER (OPTION PH OR DPH)	P5 (2)	kW	16,2	-	24,9	24,9	31,9	31,9	31,9	31,9
MAXIMUM PUMP ABSORBED CURRENT (OPTION PH OR DPH)		A	28,6	-	42,4	42,4	53,5	53,5	53,5	53,5
HYDRAULIC CONNECTIONS (VICTAULIC)		DN	100	-	100	125	125	150	150	150
FAN SECTION (AXIAL)										
FANS		nr.	4	-	6	6	6	8	8	10
CONDENSER COIL		nr.	4	-	6	6	6	8	8	10
MAXIMUM FANS ABSORBED POWER	EC	kW	8,16	-	12,24	12,24	12,24	16,32	16,32	20,40
MAXIMUM FANS ABSORBED CURRENT		A	13,84	-	20,76	20,76	20,76	27,68	27,68	34,60
TOTAL AIR FLOW		m3/h	79852	-	19778	119778	119778	159704	159704	199630
TOTAL ELECTRIC DATA										
MAXIMUM ABSORBED CURRENT (F.L.A) (4)		A	231,6	-	363,4	383,4	455,4	523,2	551,2	659,0
MAXIMUM PEAK CURRENT (L.R.A) (4)		A	666,8	-	1039,7	1146,7	1254,7	1380,6	1489,6	1634,5
MAXIMUM PEAK CURRENT WITH SOFT START (L.R.A) (4)		A	565,2	-	881,7	969,3	1066,1	1176,0	1266,8	1398,3
NOISE DATA										
SOUND PRESSURE FOR STANDARD CONFIGURATION (4) (5)		dB(A)	65,0	-	69,1	69,1	68,0	68,6	69,4	69,7
SOUND PRESSURE FOR LOW NOISE CONFIGURTION (4) (5)		dB(A)	61,9	-	65,3	65,3	64,5	65,3	65,8	66,4
SOUND PRESSURE FOR SUPER LOW NOISE CONFIGURTION (4) (5)		dB(A)	60,6	-	64,5	64,5	63,5	64,1	64,8	65,3
DIMENSIONS AND WEIGHT										
LENGTH		mm	2910	-	4600	4600	4600	5900	5900	7200
WIDTH		mm	2210	-	2210	2210	2210	2210	2210	2210
HEIGHT		mm	2500	-	2500	2500	2500	2500	2500	2500
WEIGHT EMPTY FOR STANDARD CONFIGURATION (4)		kg	3050	-	4000	4300	4500	5250	5400	6300
WEIGHT OPERATIVE FOR STANDARD CONFIGURATION (4)		kg	3150	-	4150	4470	4700	5500	5650	6580

Data referred to:

(1) Data referred to Inlet/Outlet water temperature = +12/7 °C, ambient temperature = +35°C

(2) Available pressure can be calculated from Hitema Online Selection Software

(3) SEPR: data comply with the European Regulation (EU) 2016/2281, referring to high temperature process chillers in the configuration with brazed plate or shell and tube evaporator and without pump. Any added option that modify cooling capacity or absorbed power of the chiller will not be considered in the SEPR value (4) Data referred to standard chiller configuration NP (chiller without pump) and considering EC fans

(5) Sound pressure level referred to measures according to normative ISO3744, pressure level at distance of 10 m, referred to free field on reflecting surface.

(6) Data referred to Inlet/Outlet water temperature = +22/15 °C, ambient temperature = +35°C

**Model 663 is the only one equipped with brazed plate evaporators instead of shell and tube in order to obtain a compact design

***Model 983/F24 and 993/F24 are designed with 3 independent refrigerant circuits and 3 compressors each one with 50-75-100 partition steps


اطلاعات فنی | TECHNICAL DATA

PERFORMANCES		Model	963/F12	973/F12	983/F14	993/F16	9103/F18	9113/F18	983/F24***	993/F24***
NOMINAL COOLING CAPACITY (1)	ECO.M(3)	kW	898	1003	1160	1327	1438	-	1764	1980
TOTAL NOMINAL ABSORBED POWER (1)		kW	229,68	269,20	302,94	333,94	388,10	-	440,10	506,28
EER (1)		kW/kW	3,53	3,41	3,50	3,62	3,38	-	3,61	3,57
NOMINAL WATER FLOW		m3/h	154,48	172,48	199,58	228,26	247,25	-	303,43	340,62
EVAPORATOR PRESSURE DROP		kPa	68	69	73	81	90	-	74	90
NOMINAL COOLING CAPACITY (6)	NE.M(3)	kW	1070	1194	1389	1596	1738	-	2073	2244
TOTAL NOMINAL ABSORBED POWER (6)		kW	229,0	275,0	305,0	349,0	408,0	-	445,0	520,0
EER (6)		kW/kW	4,22	3,99	4,16	4,18	3,91	-	4,20	3,94
NOMINAL WATER FLOW		m3/h	131,40	146,70	170,70	196,10	213,50	-	254,70	275,80
EVAPORATOR PRESSURE DROP		kPa	71	64	54	60	97	-	71	60
HYDRAULIC SECTION										
WATER FLOW RANGE		m3/h	108÷195	108÷195	123÷247	144÷287	154÷307	-	185÷370	185÷370
MAXIMUM PUMP ABSORBED POWER (OPTION WP OR DP)	P3 (2)	kW	23,5	23,5	23,5	0,0	0,0	-	0,0	0,0
MAXIMUM PUMP ABSORBED CURRENT (OPTION WP OR DP)		A	39,0	39,0	39,0	0,0	0,0	-	0,0	0,0
MAXIMUM PUMP ABSORBED POWER (OPTION PH OR DPH)	P5 (2)	kW	39,1	39,1	39,1	NA	NA	-	NA	NA
MAXIMUM PUMP ABSORBED CURRENT (OPTION PH OR DPH)		A	65,6	65,6	65,6	NA	NA	-	NA	NA
HYDRAULIC CONNECTIONS (VICTAULIC)		DN	150	150	200	200	200	-	250	250
FAN SECTION (AXIAL)										
FANS		nr.	12	12	14	16	18	-	24	24
CONDENSER COIL		nr.	12	12	14	16	18	-	12	12
MAXIMUM FANS ABSORBED POWER	EC	kW	24,48	24,48	28,56	32,64	36,72	-	48,96	48,96
MAXIMUM FANS ABSORBED CURRENT		A	41,52	41,52	48,44	55,36	62,28	-	83,04	83,04
TOTAL AIR FLOW		m3/h	239556	239556	279482	319408	359334	-	435888	435888
TOTAL ELECTRIC DATA										
MAXIMUM ABSORBED CURRENT (F.L.A) (4)		A	786,8	886,8	954,6	962,4	1202,2	-	1443,6	1443,6
MAXIMUM PEAK CURRENT (L.R.A) (4)		A	2370,4	2637,4	3167,3	3171,2	3705,1	-	3636,8	3636,8
MAXIMUM PEAK CURRENT WITH SOFT START (L.R.A) (4)		A	1999,8	2231,6	2663,3	2667,2	3131,1	-	3132,8	3132,8
NOISE DATA										
SOUND PRESSURE FOR STANDARD CONFIGURATION (4) (5)		dB(A)	70,6	71,3	72,1	72,2	72,8	-	73,6	73,6
SOUND PRESSURE FOR LOW NOISE CONFIGURTION (4) (5)		dB(A)	67,2	67,7	68,5	68,7	69,3	-	69,4	69,4
SOUND PRESSURE FOR SUPER LOW NOISE CONFIGURTION (4) (5)		dB(A)	66,1	66,8	67,5	67,7	68,3	-	68,8	68,8
DIMENSIONS AND WEIGHT										
LENGTH		mm	8500	8500	9800	11100	12790	-	12880	12880
WIDTH		mm	2210	2210	2210	2210	2210	-	2210	2210
HEIGHT		mm	2500	2500	2500	2500	2500	-	2500	2500
WEIGHT EMPTY FOR STANDARD CONFIGURATION (4)		kg	7100	7250	8000	9200	9400	-	11300	11600
WEIGHT OPERATIVE FOR STANDARD CONFIGURATION (4)		kg	7400	7600	8350	9600	9800	-	11800	12100

Data referred to:

(1) Data referred to Inlet/Outlet water temperature = +12/7 °C, ambient temperature = +35°C

(2) Available pressure can be calculated from Hitema Online Selection Software

(3) SEPR: data comply with the European Regulation (EU) 2016/2281, referring to high temperature process chillers in the configuration with brazed plate or shell and tube evaporator and without pump. Any added option that modify cooling capacity or absorbed power of the chiller will not be considered in the SEPR value (4) Data referred to standard chiller configuration NP (chiller without pump) and considering EC fans

(5) Sound pressure level referred to measures according to normative ISO3744, pressure level at distance of 10 m, referred to free field on reflecting surface.

(6) Data referred to Inlet/Outlet water temperature = +22/15 °C, ambient temperature = +35°C

**Model 663 is the only one equipped with brazed plate evaporators instead of shell and tube in order to obtain a compact design

***Model 983/F24 and 993/F24 are designed with 3 independent refrigerant circuits and 3 compressors each one with 50-75-100 partition steps